





Rev	AWO #	Description	Date	Appr
-		RELEASED	4/6/05	
A		REVISED SHAPE	3/20/08	
B		REDRAWING	4/02/08	

APPROVED: _____
DATE: _____ TITLE: _____



SPECIFICATIONS:

Material:

Insulator: PBT, glass reinforced, rated UL 94V-0

Insulator color: Black

Contacts: Phosphor Bronze

Plating:

G = Gold flash over Nickel underplate overall

T = Tin over Copper underplate overall

Electrical:

Operating voltage: 250 VAC max

Current rating: 3 Amp max

Contact resistance: 30 mohms max

Insulation resistance: 1,000 Mohms min

Dielectric withstanding voltage: 650 VAC for 1 minute

Temperature Rating:

Operating temperature: -55°C to +105°C

Environmental:

Lead free, RoHS compliant



UNLESS OTHERWISE SPECIFIED
ALL DIMENSIONS ARE INCHES [MM]
TOLERANCES: EXCEPT AS NOTED
INCHES HOLES
X ± .10 ØXX ± .10
.XX ± .020 ØXXX ± .015
.XXX ± .015

TITLE
.100 [2.54] MINI SHUNT, OPEN TOP
.315 [8.00] HEIGHT

ADAM TECH
909 Rahway Avenue, Union, NJ 07083
Phone: 908-687-5000 Fax: 908-687-5710

APPROVALS	DATE	SIZE	PART NO.	REV.
DRAWN	SS	4/6/05	MSDB-X	B
CHECKED				
APPROVED				

REF: _____ SCALE: NTS SHEET 1 OF 1