



APPROVED: _____




DATE: _____ TITLE: _____

Rev	AWO #	Description	Date	Appr
-		RELEASED	11/2/20	
A		UPDATE SPEC.	8/31/21	JJ/RC
B		UPDATE DIM	5/27/22	WX/MC



RECOMMENDED PANEL CUT		
Z	Y	X
.028~.049 [0.70~1.25]	.358~.362 [9.10~9.20]	.535~.543 [13.60~13.80]
.049~.079 [1.25~2.00]	.358~.362 [9.10~9.20]	.543~.551 [13.80~14.00]
.079~.118 [2.00~3.00]	.358~.362 [9.10~9.20]	.551~.555 [14.00~14.10]


*We keep the right to alter the dimension without notice.



SW-R3-1A-A-XX-0

	Actuator Color
BLANK	Standard Black
W	White
R	Red

	Actuator Markings
1	
2	
3	
4	
5	



CIRCUIT DIAGRAM
(SPST) ON-OFF

SPECIFICATIONS:

Body: Nylon 66, Color Black, Rated UL 94V-0

Terminal: Brass, Silver plated

Button: Nylon 66, Solid color, White color markings. (See Chart)

Electrical:

The rated load: 250V AC, 3A

125V AC, 6A

Contact resistance: 50 mohms max

Insulation resistance: 100 Mohms min

Dielectric withstanding voltage: 1500 VAC/5S min

Mechanical:

Electrical life: 10000 Cycles min

Temperature Rating:

Operating temperature: -25°C to +85°C

Environmental:

Lead free, RoHS compliant



Replace "x" in P/N with the corresponding switch color and marking

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE INCHES [MM]. TOLERANCES: EXCEPT AS NOTED		
INCHES		HOLES
.X ±.10	Ø.X ±.10	
.XX ±.020	Ø.XX ±.015	
.XXX ±.015	Ø.XXX ±.010	

ADAM TECH

909 Rahway Avenue,
Union, NJ 07083
Phone: 908-687-5000
Fax: 908-687-5710

DRAWN	OW	11/2/20
CHECKED	AC	11/2/20
APPROVED		

TITLE
**SWITCH, SUB MINIATURE ROCKER, SPST,
ON-OFF, SOLDER TYPE**

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY AND SHOULD NOT BE USED WITHOUT PRIOR WRITTEN PERMISSION FROM ADAM TECH

SIZE X	PART NO. SW-R3-1A-A-XX-0	REV. B
REF: S00206C	SCALE: NTS	SHEET 1 OF 1