



### Main Product Characteristics

|               |                     |
|---------------|---------------------|
| $V_{(BR)DSS}$ | 100V                |
| $R_{DS(ON)}$  | 185m $\Omega$ (max) |
| $I_D$         | 3A                  |



SOT-223



Schematic Diagram

### Features and Benefits

- Advanced MOSFET process technology
- Ideal for high efficiency switched mode power supplies
- Low on-resistance with low gate charge
- Fast switching and reverse body recovery



### Description

The GSFL1004 utilizes the latest techniques to achieve high cell density and low on-resistance. These features make this device extremely efficient and reliable for use in high efficiency switch mode power supply and a wide variety of other applications.

### Absolute Maximum Ratings ( $T_C=25^\circ\text{C}$ unless otherwise specified)

| Parameter  | Symbol          | Max.        | Unit                |
|--|-----------------|-------------|---------------------|
| Drain-Source Voltage                                 | $V_{DS}$        | 100         | V                   |
| Gate-Source Voltage                                  | $V_{GS}$        | $\pm 20$    | V                   |
| Drain Current-Continuous ( $T_C=25^\circ\text{C}$ )  | $I_D$           | 3           | A                   |
| Drain Current-Continuous ( $T_C=100^\circ\text{C}$ ) |                 | 1.8         | A                   |
| Drain Current-Pulsed <sup>1</sup>                    | $I_{DM}$        | 12          | A                   |
| Power Dissipation ( $T_C=25^\circ\text{C}$ )         | $P_D$           | 1.78        | W                   |
| Power Dissipation-Derate Above 25 $^\circ\text{C}$   |                 | 0.014       | W/ $^\circ\text{C}$ |
| Thermal Resistance, Junction-to-Ambient              | $R_{\theta JA}$ | 70          | $^\circ\text{C/W}$  |
| Thermal Resistance, Junction-to-Case                 | $R_{\theta JC}$ | 30          | $^\circ\text{C/W}$  |
| Storage Temperature Range                            | $T_{STG}$       | -50 To +150 | $^\circ\text{C}$    |
| Operating Junction Temperature Range                 | $T_J$           | -50 To +150 | $^\circ\text{C}$    |


**Electrical Characteristics** ( $T_J=25^\circ\text{C}$  unless otherwise specified)

| Parameter   | Symbol                       | Conditions   | Min. | Typ. | Max.      | Unit                 |
|---|------------------------------|--|------|------|-----------|----------------------|
| <b>Off Characteristics</b>                                    |                              |  |      |      |           |                      |
| Drain-Source Breakdown Voltage                                | $BV_{DSS}$                   | $V_{GS}=0V, I_D=250\mu A$                            | 100  | -    | -         | V                    |
| $BV_{DSS}$ Temperature Coefficient                            | $\Delta BV_{DSS}/\Delta T_J$ | Reference to $25^\circ\text{C}$ ,<br>$I_D=1mA$       | -    | 0.1  | -         | $V/^\circ\text{C}$   |
| Drain-Source Leakage Current                                  | $I_{DSS}$                    | $V_{DS}=100V, V_{GS}=0V,$<br>$T_J=25^\circ\text{C}$  | -    | -    | 1         | $\mu A$              |
|   |                              | $V_{DS}=80V, V_{GS}=0V,$<br>$T_J=125^\circ\text{C}$  | -    | -    | 10        | $\mu A$              |
| Gate-Source Leakage Current                                   | $I_{GSS}$                    | $V_{GS}=\pm 20V, V_{DS}=0V$                          | -    | -    | $\pm 100$ | nA                   |
| <b>On Characteristics</b>                                     |                              |  |      |      |           |                      |
| Static Drain-Source On-Resistance                             | $R_{DS(ON)}$                 | $V_{GS}=10V, I_D=2A$                                 | -    | 160  | 185       | m $\Omega$           |
|   |                              | $V_{GS}=4.5V, I_D=1A$                                | -    | 170  | 195       |                      |
| Gate Threshold Voltage  | $V_{GS(th)}$                 | $V_{GS}=V_{DS}, I_D=250\mu A$                        | 1.2  | 1.8  | 2.5       | V                    |
| $V_{GS(th)}$ Temperature Coefficient                          | $\Delta V_{GS(th)}$          |  | -    | -4   | -         | mV/ $^\circ\text{C}$ |
| Forward Transconductance                                      | gfs                          | $V_{DS}=10V, I_D=1A$                                 | -    | 5    | -         | S                    |
| <b>Dynamic and Switching Characteristics</b>                  |                              |  |      |      |           |                      |
| Total Gate Charge <sup>2,3</sup>                              | $Q_g$                        | $V_{DS}=50V, I_D=2A,$<br>$V_{GS}=10V$                | -    | 13.4 | 21        | nC                   |
| Gate-Source Charge <sup>2,3</sup>                             | $Q_{gs}$                     |  | -    | 2.9  | 6         |                      |
| Gate-Drain Charge <sup>2,3</sup>                              | $Q_{gd}$                     |  | -    | 1.7  | 4         |                      |
| Turn-On Delay Time <sup>2,3</sup>                             | $t_{d(on)}$                  | $V_{DD}=30V, R_G=3.3\Omega,$<br>$V_{GS}=10V, I_D=1A$ | -    | 1.6  | 3         | nS                   |
| Rise Time <sup>2,3</sup>                                      | $t_r$                        |  | -    | 6.6  | 13        |                      |
| Turn-Off Delay Time <sup>2,3</sup>                            | $t_{d(off)}$                 |  | -    | 11.5 | 22        |                      |
| Fall Time <sup>2,3</sup>                                      | $t_f$                        |  | -    | 3.6  | 7         |                      |
| Input Capacitance   | $C_{iss}$                    | $V_{DS}=50V, V_{GS}=0V,$<br>$F=1MHz$                 | -    | 820  | 1190      | pF                   |
| Output Capacitance  | $C_{oss}$                    |  | -    | 35   | 55        |                      |
| Reverse Transfer Capacitance                                  | $C_{rss}$                    |  | -    | 20   | 30        |                      |
| Gate Resistance   | $R_g$                        | $V_{GS}=0V, V_{DS}=0V,$<br>$F=1MHz$                  | -    | 1.3  | 2.6       | $\Omega$             |
| <b>Drain-Source Diode Characteristics and Maximum Ratings</b> |                              |  |      |      |           |                      |
| Continuous Source Current                                     | $I_S$                        | $V_G=V_D=0V,$<br>Force Current                       | -    | -    | 3         | A                    |
| Pulsed Source Current   | $I_{SM}$                     |  | -    | -    | 6         | A                    |
| Diode Forward Voltage   | $V_{SD}$                     | $V_{GS}=0V, I_S=1A,$<br>$T_J=25^\circ\text{C}$       | -    | -    | 1         | V                    |


Notes:

1. Repetitive rating: Pulsed width limited by maximum junction temperature.
2. The data tested by pulsed, pulse width  $\leq 300\mu\text{s}$ , duty cycle  $\leq 2\%$ .
3. Essentially independent of operating temperature.


**Typical Electrical and Thermal Characteristic Curves**




**Figure 1. Continuous Drain Current vs. T<sub>c</sub>**




**Figure 2. Normalized R<sub>DS(ON)</sub> vs. T<sub>J</sub>**




**Figure 3. Normalized V<sub>th</sub> vs. T<sub>J</sub>**



**Figure 4. Gate Charge Waveform**




**Figure 5. Typical Output Characteristics**




**Figure 6. Transfer Characteristics**


**Typical Electrical and Thermal Characteristic Curves**




**Figure 7. Normalized Transient Impedance**



**Figure 8. Maximum Safe Operation Area**




**Figure 9. Switching Time Waveform**




**Figure 10. Gate Charge Waveform**

### Package Outline Dimensions (SOT-223)



| Symbol | Dimensions In Millimeters |       | Dimensions In Inches |       |
|--------|---------------------------|-------|----------------------|-------|
|        | Min.                      | Max.  | Min.                 | Max.  |
| A      | 1.500                     | 1.800 | 0.060                | 0.071 |
| A1     | 0.000                     | 0.120 | 0.000                | 0.005 |
| A2     | 1.450                     | 1.750 | 0.057                | 0.069 |
| b      | 0.600                     | 0.820 | 0.024                | 0.032 |
| c      | 0.200                     | 0.350 | 0.008                | 0.014 |
| D      | 6.200                     | 6.700 | 0.244                | 0.264 |
| D1     | 2.900                     | 3.100 | 0.114                | 0.122 |
| E      | 3.300                     | 3.700 | 0.130                | 0.146 |
| E1     | 6.700                     | 7.300 | 0.264                | 0.287 |
| e      | 2.30 BSC                  |       | 0.091 BSC            |       |
| e1     | 4.400                     | 4.700 | 0.173                | 0.185 |
| L      | 0.900                     | 1.150 | 0.035                | 0.045 |
| θ      | 0°                        | 10°   | 0°                   | 10°   |

### Recommended Pad Layout



### Order Information

| Device   | Package | Marking | Carrier     | Quantity         |
|----------|---------|---------|-------------|------------------|
| GSFL1004 | SOT-223 | DL0910  | Tape & Reel | 3,000 Pcs / Reel |

For more information, please contact us at: [inquiry@goodarksemi.com](mailto:inquiry@goodarksemi.com)